

**zehnder** *kleo*

**zehnder**

always  
around you

Heating


Cooling

Fresh Air


Clean Air



## Overview of models – Horizontal version



Single row



Double row

### Product description

The delicate Zehnder Kleo with horizontal lines.

### Benefits

- Retrofitting models for existing connections
- Open, transparent construction
- Safety
- Radiant heat with feel-good factor
- Energy-efficient for use in low-temperature systems

#### Horizontal version, single row

Model	H	D	Thermal output
	mm	mm	EN 442 ① W
KLH-022	231	55	279
KLH-028	297	55	371
KLH-035	363	55	466
KLH-042	429	55	564
KLH-048	495	55	654
KLH-055	561	55	739
KLH-061	627	55	824
KLH-068	693	55	909
KLH-075	759	55	993
KLH-081	825	55	1067
KLH-088	891	55	1159
KLH-094	957	55	1241
KLH-101	1023	55	1323
KLH-108	1089	55	1405
KLH-114	1155	55	1485
KLH-121	1221	55	1566
KLH-127	1287	55	1646
KLH-134	1353	55	1725
KLH-141	1419	55	1804
KLH-147	1485	55	1882
KLH-154	1551	55	1960
KLH-160	1617	55	2038
KLH-167	1683	55	2115
KLH-174	1749	55	2191
KLH-180	1815	55	2267
KLH-187	1881	55	2342
KLH-193	1947	55	2417
KLH-200	2013	55	2492
KLH-207	2079	55	2566
KLH-213	2145	55	2639

#### Horizontal version, double row

Model	H	D	Thermal output
	mm	mm	EN 442 ① W
KLHD-022	231	72	540
KLHD-028	297	72	670
KLHD-035	363	72	795
KLHD-042	429	72	917
KLHD-048	495	72	1036
KLHD-055	561	72	1153
KLHD-061	627	72	1268
KLHD-068	693	72	1382
KLHD-075	759	72	1494
KLHD-081	825	72	1604
KLHD-088	891	72	1713
KLHD-094	957	72	1821
KLHD-101	1023	72	1928
KLHD-108	1089	72	2034
KLHD-114	1155	72	2140
KLHD-121	1221	72	2244
KLHD-127	1287	72	2347
KLHD-134	1353	72	2450
KLHD-141	1419	72	2552
KLHD-147	1485	72	2653
KLHD-154	1551	72	2754
KLHD-160	1617	72	2854
KLHD-167	1683	72	2954
KLHD-174	1749	72	3053
KLHD-180	1815	72	3152
KLHD-187	1881	72	3250
KLHD-193	1947	72	3347
KLHD-200	2013	72	3444
KLHD-207	2079	72	3541
KLHD-213	2145	72	3637


H = Height

L = Length


D = Depth

① = Thermal output with a length of 1000 mm, measured according to EN 442,  $\Delta T$  50 K (75/65/20°C)

## Overview of models – Vertical version



Single row



Double row

### Product description

Light and transparent: Zehnder Kleo belies its delicate construction with high output values.

### Benefits

- Retrofitting models for existing connections
- Open, transparent construction
- Safety
- Accessories for use as a bathroom radiator
- Use as a room divider
- Radiant heat with feel-good factor
- Energy-efficient for use in low-temperature systems

#### Vertical, single row

Model	H	D	Thermal output
	mm	mm	EN 442 ① W
KLV-050	500	55	22.3
KLV-060	600	55	26.1
KLV-070	700	55	29.9
KLV-080	800	55	33.7
KLV-090	900	55	37.4
KLV-100	1000	55	41.1
KLV-110	1100	55	44.8
KLV-120	1200	55	48.5
KLV-130	1300	55	52.1
KLV-140	1400	55	55.8
KLV-150	1500	55	59.4
KLV-160	1600	55	63.0
KLV-170	1700	55	68.8
KLV-180	1800	55	70.2
KLV-190	1900	55	73.9
KLV-200	2000	55	77.5
KLV-210	2100	55	81.1
KLV-220	2200	55	84.7
KLV-230	2300	55	88.3
KLV-240	2400	55	92.0
KLV-250	2500	55	95.6
KLV-260	2600	55	99.3
KLV-270	2700	55	103.0
KLV-280	2800	55	107.0
KLV-290	2900	55	110.0
KLV-300	3000	55	114.0

#### Vertical, double row

Model	H	D	Thermal output
	mm	mm	EN 442 ① W
KLVD-050	500	72	34.3
KLVD-060	600	72	40.4
KLVD-070	700	72	48.4
KLVD-080	800	72	52.3
KLVD-090	900	72	58.1
KLVD-100	1000	72	63.8
KLVD-110	1100	72	69.4
KLVD-120	1200	72	74.9
KLVD-130	1300	72	80.3
KLVD-140	1400	72	85.7
KLVD-150	1500	72	91.0
KLVD-160	1600	72	96.1
KLVD-170	1700	72	101.0
KLVD-180	1800	72	106.0
KLVD-190	1900	72	111.0
KLVD-200	2000	72	116.0
KLVD-210	2100	72	121.0
KLVD-220	2200	72	128.0
KLVD-230	2300	72	131.0
KLVD-240	2400	72	135.0
KLVD-250	2500	72	140.0
KLVD-260	2600	72	144.0
KLVD-270	2700	72	149.0
KLVD-280	2800	72	153.0
KLVD-290	2900	72	185.0
KLVD-300	3000	72	162.0

H = Height

L = Length

D = Depth

① = Thermal output per section, measured according to EN 442,  $\Delta T$  50 K (75/65/20°C)

ZGIS-LEAF-Kleo V0811, en, subject to change without notice



Avenida da Conduta, 836  
4420-619 GONDOMAR  
PORTUGAL

Tel: (+351) 22 372 03 92  
info@climaconforto.pt

Fax: (+351) 22 379 09 08  
www.climaconforto.pt